LISTING OF THE CLAIMS

Docket No : 59894(49991)

The following is a listing of claims as previously presented in the application. No amendments are made herein

(Original) A material for chromatographic separations comprising a
porous inorganic/organic hybrid monolith, said monolith having and an interior
area and an exterior surface, wherein said monolith is represented by:

[A]_v[B]_x (Formula I),

wherein x and y are whole number integers and A is

SiO₂/(R¹_pR²_oSiO_t)_n (Formula II) and/or SiO₂/[R³(R¹_tSiO_t)_m]_n (Formula III);

wherein R^1 and R^2 are independently a substituted or unsubstituted C_1 to C_7 alkyl group, or a substituted or unsubstituted aryl group, R^3 is a substituted or unsubstituted C_1 to C_7 alkylene, alkenylene, alkynylene, or arylene group bridging two or more silicon atoms, p and q are 0, 1, or 2, provided that p+q=1 or 2, and that when p+q=1, t=15, and when p+q=2, t=1; r is 0 or 1, provided that when r=0, t=1.5, and when r=1, t=1; m is an integer greater than or equal to 2; and n is a number from 0.01 to 100;

B is:

wherein R^4 is hydroxyl, fluorine, alkoxy, aryloxy, substituted siloxane, protein, peptide, carbohydrate, nucleic acid, or combinations thereof, R^4 is not R^1 , R^2 , or R^3 ; v is 1 or 2, provided that when v=1, t=1.5, and when v=2, t=1; and n is a number from 0.01 to 100:

said interior of said monolith having a composition of A; said exterior surface of said monolith having a composition represented by A and B, and wherein said exterior composition is between about 1 and about 99% of the composition of B and the remainder comprising A.

(Original) The material of claim 1 wherein said exterior surface has a
composition that is between about 50 and about 90% of composition B, with the
remainder comprising composition A.

Docket No.: 59894(49991)

- (Original) The material of claim 1 wherein said exterior surface has a
 composition that is between about 70 and about 90% of composition B, with the
 remainder comprising composition A.
- (Original) he material of claim 1 wherein R⁴ is hydroxyl.
- 5. (Original) The material of claim 1 wherein R⁴ is fluorine.
- 6. (Original) The material of claim 1 wherein R⁴ is methoxy.
- 7. (Original) The material of claim 1 wherein R⁴ is

wherein R^5 is a C_1 to C_6 straight, cyclic, or branched alkyl, aryl, or alkoxy group, a hydroxyl group, or a siloxane group, and R^6 is a C_1 to C_{36} straight, cyclic, or branched alkyl, aryl, or alkoxy group, wherein R^6 is unsubstituted or substituted with one or more moieties selected from the group consisting of halogen, cyano, amino, diol, nitro, ether, carbonyl, epoxide, sulfonyl, cation exchanger, anion exchanger, carbamate, amide, urea, peptide, protein, carbohydrate, nucleic acid functionalities, and combinations thereof.

- (Original) The material of claim 7 wherein R⁶ is a C₁₈ group.
- 9. (Original) The material of claim 7 wherein R⁶ is a cyanopropyl group.
- 10. (Original) The material of claim 1, having a specific surface area of about 50 to about $800 \text{ m}^2\text{/g}$.
- 11. (Original) The material of claim 1, having a specific surface area of about 190 to about $520~{\rm m}^2/{\rm g}$.
- 12. (Original) The material of claim 1, having specific pore volumes of about 0.5 to about 2.5 cm 3 /g.

 (Original) The material of claim 1, having specific pore volumes of about 1 to about 2 cm³/g.

Docket No.: 59894(49991)

- (Original) The material of claim 1, having an average pore diameter of about 35 to 500Å.
- 15. (Original) The material of claim 1, having an average pore diameter of about 100 to 300Å.
- 16. (Original) The material of claim 1, having been surface modified by polymer coating.
- (Cancelled)
- 18. (Cancelled)
- 19. (Original) The material of claim 7, having a surface concentration of R^6 greater than about $1.0 \ \mu mol/m^2$.
- 20. (Original) The material of claim 7, having a surface concentration of R^6 greater than about $2.0 \, \mu \text{mol/m}^2$.
- 21. (Original) The material of claim 7, having a surface concentration of R^6 greater than about 3.0 μ mol/m².
- 22. (Original) The material of claim 7, having a surface concentration of R^6 between about 1.0 and 3.4 μ mol/m².
- 23. (Original) The material of claim 20, having a specific surface area of about 50 to about $800 \text{ m}^2/\text{g}$.
- 24. (Original) The material of claim 20, having a specific surface area of about 190 to about $520 \text{ m}^2/\text{g}$.
- 25. (Original) The material of claim 20, having specific pore volumes of about 0.5 to about 2.5 cm³/g.
- 26. (Original) The material of claim 20, having specific pore volumes of about 1 to about 2 cm^3/g .

Application No. 10/587,598 5 Response to Non-Final Office Action of March 22, 2010

27. (Original) The material of claim 20, having an average pore diameter of about 35 to 500 Å.

Docket No : 59894(49991)

- 28. (Original) The material of claim 20, having an average pore diameter of about 100 to 300 $\mathring{\rm A}$.
- 29. (Original) The material of claim 20, which have been surface modified by polymer coating.
- 30. (Previously Presented) A method of performing a separation comprising contacting a sample with the material of claim 1.
- (Previously Presented) The method of claim 29, wherein the sample is passed through a chromatographic column containing the material of claim 1.
- 32. (Original) A separation device comprising the material of claim 1.
- 33. (Original) The separation device of claim 30, said device is selected from the group consisting of chromatographic columns, thin layer chromatographic plates, filtration membranes, sample clean up devices, solid phase organic synthesis supports, and microtiter plates.
- 34. (Original) The material of claim 1, wherein the monolith has a chromatographically enhancing pore geometry.
- (Cancelled)
- 36. (Previously Presented) A method of preparing <u>a</u> material for chromatographic separations of claim 1,

the method comprising:

- a) preparing an aqueous solution of a mixture of one or more organoalkoxysilanes and a tetraalkoxysilane in the presence of an acid catalyst, and a surfactant or combination of surfactants to produce a polyorganoalkoxysiloxane;
- b) incubating said solution, resulting in a three-dimensional gel having a continuous, interconnected pore structure;
 - c) aging the gel at a controlled pH and temperature to yield a solid monolith material;

Application No. 10/587,598 6 Response to Non-Final Office Action of March 22, 2010

 d) rinsing the monolith material with an aqueous basic solution at an elevated temperature;

e) rinsing the monolith material with water followed by a solvent exchange;

Docket No.: 59894(49991)

- f) drying the monolith material at room temperature drying and at an elevated temperature under vacuum; and
- g) replacing one or more surface C_1 to C_7 alkyl groups, substituted or unsubstituted aryl groups, substituted or unsubstituted C_1 to C_7 alkylene, alkenylene, alkynylene, or arylene groups of the monolith with hydroxyl, fluorine, alkoxy, aryloxy, or substituted siloxane groups.
- 37. (Cancelled)
- 38. (Cancelled)
- 39. (Cancelled)
- 40. (Cancelled)
- 41. (Cancelled)
- 42. (Cancelled)
- 43. (Cancelled)

(Cancelled)

(Cancelled)

45. (Cancelled)

44.

46.

- 45. (Cancelled)
- 47. (Cancelled)
- 48. (Cancelled)
- 49. (Cancelled)
- 50. (Cancelled)
- 51. (Cancelled)

52. (Original) A material for chromatographic separations of claim 1 comprising a porous inorganic/organic hybrid monolith, said monolith having and an interior area and an exterior surface, wherein said monolith is represented by:

Docket No : 59894(49991)

[A] [B] (Formula D.

wherein x and v are whole number integers and A is

SiO₂/(R¹_nR²_oSiO₄)_n (Formula II) and/or SiO₂/[R³(R¹_nSiO₄)_m]_n (Formula III);

wherein R^1 and R^2 are independently a substituted or unsubstituted C_1 to C_7 alkyl group, or a substituted or unsubstituted aryl group, R^3 is a substituted or unsubstituted C_1 to C_7 alkylene, alkenylene, alkynylene, or arylene group bridging two or more silicon atoms, p and q are 0, 1, or 2, provided that p+q=1 or 2, and that when p+q=1, t=15, and when p+q=2, t=1; r is 0 or 1, provided that when r=0, t=1.5, and when r=1, t=1; m is an integer greater than or equal to 2; and n is a number from 0.01 to 100;

B is:

SiO₂/(R⁴_vSiO_t)_n (Formula IV)

wherein R^4 is hydroxyl, fluorine, alkoxy, aryloxy, substituted siloxane, protein, peptide, carbohydrate, nucleic acid, or combinations thereof, R^4 is not R^1 , R^2 , or R^3 ; v is 1 or 2, provided that when v=1, t=1.5, and when v=2, t=1; and n is a number from 0.01 to 100:

said interior of said monolith having a composition of A; said exterior surface of said monolith having a composition represented by A and B, and wherein said exterior composition is between about 1 and about 99% of the composition of B and the remainder comprising A;

said material prepared by a process comprising:

- a) preparing an aqueous solution of a mixture of one or more organoalkoxysilanes and a tetraalkoxysilane in the presence of an acid catalyst, and a surfactant or combination of surfactants to produce a polyoreanoalkoxysiloxane;
- b) incubating said solution, resulting in a three-dimensional gel having a continuous, interconnected pore structure:

Application No. 10/587,598 8
Response to Non-Final Office Action of March 22, 2010

c) aging the gel at a controlled pH and temperature to yield a solid monolith material;

Docket No : 59894(49991)

- d) rinsing the monolith material with an aqueous basic solution at an elevated temperature;
 - e) rinsing the monolith material with water followed by a solvent exchange:
- f) drying the monolith material at room temperature drying and at an elevated temperature under vacuum; and
- g) replacing one or more surface C₁ to C₇ alkyl groups, substituted or unsubstituted aryl groups, substituted or unsubstituted C₁ to C₇ alkylene, alkenylene, alkynylene, or arylene groups of the monolith with hydroxyl, fluorine, alkoxy, aryloxy, or substituted siloxane groups.
- 53. (Original) A method of forming a porous inorganic/organic hybrid monolith comprising:
- (a) forming a porous inorganic/organic hybrid monolith having surface silicon-alkyl groups;
- (b) replacing one or more surface silicon-alkyl groups of the hybrid monolith with hydroxyl groups;
 - (c) replacing one or more surface silicon-alkyl groups with halo groups:
- (d) bonding one or more substituted siloxane groups to the surface of the hybrid monolith; and
 - (e) end-capping the surface of the hybrid monolith with trialkylhalosilane.
- (Cancelled)
- (Cancelled)
- 56. (Cancelled)